CM084-2-AMPS 9" Floor or Console Mounting Pedestal



Package Contents:

- (1) CM084-2-AMPS 9" Universal flexible mounting arm Includes threaded screws (3), screw caps (3), and machine screws (4) for connecting to AMPS pattern
- (1) AP032 Dual T-tab to AMPS horizontal adapter plate

Tools required for floor or console mounting - drill and screwdriver.

Note: Do not twist the cradle or device while mounted on top of the pedestal to adjust the steel shaft as this can break the dual T-slots.


Precaution: This solution requires drilling which may damage your vehicle. Consult with a mobile install professional prior to installation. Arkon Resources, Inc. assumes no responsibility of liability for damage to your vehicle.

Do not install this pedestal in an airbag deployment zone or where windshield vision may be impaired.


Installation Instructions

Floor or Console Mounting

Step 1. Find a safe, flat location on the interior of the vehicle's floor or console to mount the pedestal.



- Step 2. Using the base as a template, drill three 1/8" holes and attach base with the included self-tapping screws. Snap screw caps in place over the screws on the base.
- Step 3. Screw the 9" flexible steel arm securely into the base.







WARNING:

Drilling into the floor or console can permanently damage the vehicle. Use caution and consult a mobile install professional to avoid drilling into the gas tank, electrical system or other highly sensitive vehicle components.

Arkon Resources, Inc. is not responsible for any damages caused to your car, your device, or yourself due to the installation or use of the pedestal mount. Step 5. Attach the 4 hole AMPS pattern plate (if necessary) to the other end of the mounting arm with the included large hex nuts. Fasten the AMPS to dual T-tab adapter plate to the AMPS pattern plate with the included screws and nuts.



- Step 6. Adjust the gooseneck by bending with both hands to the desired location of the cradle or device.
- Step 7. Attach the dual T-slots on the back of the cradle or device to the dual T-tab adapter plate.





RESOURCES INC. The Mobile Mounting Specialists™

Consumer Hotline: (USA) (800) 841-0884 (INT'L) (626) 254-9005 Mon-Fri. 9am-5pm, PST www.arkon.com Arcadia, CA 91006 USA Made in Taiwan © Copyright 2007 Arkon Resources, Inc.